

## Moon • Galaxy • Bay

### Assembly Instructions

#### In the box:

- Fixture
- Glasses
- Installation kit containing gloves, extra screw
- Extra screws
- Bulbs (where needed)



keep the 'installation kit' until you've confirmed all components are present

**For USA:** This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

**For CANADA:** ce produit doit être installé selon le code d'installation pertinent, par une personne qui connaît bien le produit et son fonctionnement ainsi que les risques inhérents.

#### Preparation:


1. Determine your ceiling type (wood, drywall, or concrete) and use the appropriate screws (not provided).  
**For drywall,** locate ceiling joists and make sure the screws go beyond the drywall into the joist.  
**For concrete,** use masonry anchor screws.
2. Carefully unpack the fixture and check for the main fixture, spare part.



**Before starting installation, Turn off the relevant electrical power source to ensure safety.**

#### Installation:

1. Detach the metal bracket from the back of the canopy and mount it onto the ceiling, with the flat side upward. Make sure the electrical wires are exposed near the bracket.



**If your ceiling is sloped, pay attention to the 'Lower side'/'Higher side' labels.**

2. Twist the GND wire coming out of your electrical box with the GND wire of the light fixture. Use the twist connector attached to the GND wire from the bracket. in fixture that utilizes strip-led in the US/CA - connect the GND wire that is coming out of the driver as well.
3. For the next stage you will need a second person to help you hold the fixture up while you connect the electrical wire to the fixture. >>



**Please wear the gloves provided in order to prevent leaving fingerprints on the canopy.**



4. Lift the main (or upper if two) canopy and hold it close to the bracket while connecting the wires.
5. Connect the positive (white) and negative (black) wires from your electrical box with the respective wires from the Fixture. Use the twist connector attached to the wires.
6. Before installing the glasses, make sure to verify that everything is functioning properly.

#### Assembly of Glasses

1. Carefully unwrap each glass pack, taking note that each pack contains 2 wide and 2 narrow glasses. Pair them oppositely, starting with the narrow ones,
2. Ensure that the glossy side faces outwards and the matte side faces inwards. If there is any white residue, do not attempt to remove it.



#### Adjustment :

1. To adjust the wire length, locate the small plastic screw within the canopy corresponding to each wire. Carefully rotate it to free the wire, make the necessary adjustments, and then secure it back in place. Handle with caution to prevent any damage.
2. In case of an uneven ceiling, use white or clear silicone to bridge any space between the ceiling and canopy.
3. If your fixture has a double canopy, repeat the installation process for both the upper and lower canopy.

#### Maintenance and Care

1. **Dust:** Use a soft, dry cloth to regularly dust your fixture.
2. **Metal:** Wipe with a damp mat.

**For Future including LED BULB (not strips) always purchase the same type for consistency in performance. Specifically, look for LED E27/E26 15w bulb with 1570 lumens, 3000k, and dimmable features**



ENJOY!

WhatsApp: +972-52-5279674 • Email: miri@shimale.co.il  
www.shimale.co.il • www.etsy.com/shop/shimaleLightArt

**SHIMALE PELEG**  
LIGHT IN ART